



Phone: (07) 4927 9150
Email: rifen.boats@bigpond.com
Website: www.rifenmarine.com.au

Boat Details

| | | | |
|------------|-------------------|--------------|----------------------------|
| Price | POA | Boat Brand | Mercury |
| Model | 200 HP Pro XS | Length | 0.00 |
| Year | 2021 | Category | Boat Engines and Outboards |
| Hull Style | | Hull Type | |
| Power Type | | Stock Number | 0 |
| Condition | New | State | Queensland |
| Suburb | NORTH ROCKHAMPTON | Engine Make | Mercury |

Description

The 200hp Pro XS provides hard-charging performance to put you out front and keep you there. Pro XS is the choice of tournament anglers and performance enthusiasts who don't like coming second. Mercury V-8 Pro XS models transform every drop of fuel into performance delivering class leading fuel economy at cruising speed and wide-open throttle. Advanced Range Optimisation (ARO) utilises closed-loop fuel control to precisely adjust the fuel mixture and deliver the best possible efficiency. All Pro XS FourStroke models now come with a 3+3=6 Year factory warranty.ENGINE DETAILS

Maximized power, torque and overall performance for spectacular acceleration and top speed. Great for bass and multi-species fishing boats. SPECIFICATIONS - 200

HP / kW
• 200 / 149

Engine type
• V-8

MidSection
• Conventional MidSection

Displacement (CID/CC)
• 279 CID

Displacement (L)
• 4.6L

Cylinder Configuration
• V-8 [64 degree] with Dual Overhead Cam [DOHC] and 32-valves

Full throttle RPM
• 5600-6200

Air induction
• Performance-Tuned Long-Runner Intake Manifold

Fuel induction system
• Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization

Alternator amp / Watt
• 85-amp (1071 Watt) with Idle Charge

Recommended fuel
• Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum

Recommended oil
• NMMA Certified FCW SAE 10W-30

Engine protection operator warning system
• SmartCraft Engine Guardian

Compatible with SmartCraft digital technology
• Yes

Starting
• Electric Start with SmartStart Protection

Controls
• Remote Mechanical or Digital Throttle & Shift (DTS)

Steering
• Big Tiller (optional)
• Hydraulic (standard)
• Power (optional)

Shaft length

- 20" / 508 mm
- 25" / 635 mm

Gearcase ratio

- 1.75:1 (TorqueMaster or 5.44"); 1.85:1 (4.8")

Dry weight *Lightest model available

- 505 lbs / 229 kgs

CARB star rating

- 3

Bore and stroke

- 3.6 in x 3.4 in / 92 mm x 86 mm

Ignition

- SmartCraft PCM 112 Digital Inductive

Cooling system

- Water-cooled with thermostat

Gear shift

- F-N-R

Gearcase options

- 20": 4.8"
- 20": TorqueMaster
- 25": 5.44"

Trim system

- Power trim and tilt

Exhaust system

- Through prop

Color

- Phantom Black

Lubrication system

- Wet sump

Oil Capacity

- 7.0 Quarts / 6.6 Liters

Maximum Trim Range

- 20° (-6° to 14°)

Maximum Tilt Range

- 73° (-6° to 67°)

Engine Details

| | |
|--------------|---------|
| Engine Make | Mercury |
| Displacement | 4.6 |
| Horse Power | 200 |