



Phone: (07) 4927 9150  
Email: rifen.boats@bigpond.com  
Website: www.rifenmarine.com.au

Boat Details

Price	POA	Boat Brand	Mercury
Model	250 HP	Length	0.00
Year	2021	Category	Boat Engines and Outboards
Hull Style		Hull Type	
Power Type		Stock Number	0
Condition	New	State	Queensland
Suburb	NORTH ROCKHAMPTON	Engine Make	

Description

The new Mercury 250hp FourStroke is precision engineered from skeg to cowl. Packed with advanced technology to improve all aspects of performance and reliability. the Robust 4.6 Litre V-8 engine is designed to minimise weight and maximise fuel economy. Delivering Mercury's best ever FourStroke hole shot, top speed and fuel efficiency. The 250hp FourStroke now comes with a 3+3=6 Year factory warranty.ENGINE DETAILS

Quick-revving double-overhead camshaft design and deep-breathing intake deliver thrilling and satisfying performance. Great for aluminum console, deck, inflatable rigid hull, inshore fishing, offshore fishing, and runabout boats and tritoons.SPECIFICATIONS - 250 HP / kW

- 250 / 186

Engine type

- V-8

MidSection

- Conventional MidSection

Displacement (CID/CC)

- 279 CID

Displacement (L)

- 4.6L

Cylinder Configuration

- V-8 [64 degree] with Dual Overhead Cam [DOHC] and 32-valves

Full throttle RPM

- 5200-6000

Air induction

- Performance-Tuned Long-Runner Intake Manifold

Fuel induction system

- Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization

Alternator amp / Watt

- 85-amp (1071 Watt) with Idle Charge

Recommended fuel

- Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum

Recommended oil

- NMMA Certified FCW SAE 10W-30

Engine protection operator warning system

- SmartCraft Engine Guardian

Compatible with SmartCraft digital technology

- Yes

Starting

- Electric Start with SmartStart Protection

Controls

- Remote Mechanical or Digital Throttle & Shift (DTS)

Steering

- Big Tiller (optional)
- Hydraulic (standard)
- Power (optional)

Shaft length

- 20" / 508 mm
- 25" / 635 mm
- 30" / 762 mm

Gearcase ratio

- 1.75:1

Dry weight \*Lightest model available

- 527 lbs / 239 kgs

CARB star rating

- 3

Bore and stroke

- 3.6 in x 3.4 in / 92 mm x 86 mm

Ignition

- SmartCraft PCM 112 Digital Inductive

Cooling system

- Water-cooled with thermostat

Gear shift

- F-N-R

Gearcase options

- 5.44"

Trim system

- Power trim and tilt

Exhaust system

- Through prop

Counter Rotation

- Available

Color

- Cold Fusion White
- Pearl Fusion White
- Phantom Black
- Warm Fusion White

Lubrication system

- Integrated wet sump

Oil Capacity

- 7.0 Quarts / 6.6 Liters

Maximum Trim Range

- 20° (-6° to 14°)

Maximum Tilt Range

- 73° (-6° to 67°)

Engine Details

Displacement4.6

Horse Power250

SteeringBig Tiller (optional), Hydraulic (standard), Power (optional)

Fuel Capacity6.6