Rifen Marine

Phone: (07) 4927 9150

Email: rifen.boats@bigpond.com Website: www.rifenmarine.com.au



Boat Details

Price POA Boat Brand Mercury
Model 250 HP Length 0.00

Year 2021 Category Boat Engines and Outboards

Hull Style Hull Type
Power Type Stock Nur

Stock Number 0

ConditionNewStateQueenslandSuburbNORTH ROCKHAMPTONEngine MakeMercury

Description

The new Mercury V-8 SeaPro outboard models bring more of everything to the job—more displacement, more power, more efficiency and more durability. The impressive muscle of our new V-8 4.6-litre powerhead is specifically designed for commercial duty and delivers our best-ever fuel economy and FourStroke performance. The combination of ample torque and low weight makes these engines ideal for heavily-loaded boats. Guaranteed to do its job, so you can do yours. Mercury SeaPro FourStroke models come with a 2+1=3 year commercial factory warranty. ENGINE DETAILS

Offers simple, seamless repower rigging. Engineered for commercial fishing vessels, commercial workboats and law-enforcement boats. SPECIFICATIONS - 250

HP / kW

• 250/186

Engine type

• V-8

MidSection

• Conventional MidSection

Displacement (CID/CC)

• 279 CID

Displacement (L)

• 4.6L

Cylinder Configuration

• V-8 [64 degree] with Dual Overhead Cam [DOHC] and 32-valves

Full throttle RPM

• 4800-5600

Air induction

• Performance-Tuned Long-Runner Intake Manifold

Fuel induction system

• Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization

Alternator amp / Watt

• 85-amp (1071 Watt) with Idle Charge

Recommended fuel

Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum

Recommended oil

• NMMA Certified FCW SAE 25W-40 (Optional 10W-30 for Cold Conditions)

Engine protection operator warning system

• SmartCraft Engine Guardian

Compatible with SmartCraft digital technology

• Yes

Starting

• Electric Start with SmartStart Protection

Controls

• Remote Mechanical or Digital Throttle & Shift (DTS)

Steering

- Big Tiller (optional)
- Hydraulic (standard)
- Power (optional)

Shaft length • 20" / 508 mm • 25" / 635 mm • 30" / 762 mm Gearcase ratio • 1.75:1

Dry weight *Lightest model available

• 527 lbs / 239 kgs

CARB star rating

• 3

Bore and stroke

• 3.6 in x 3.4 in / 92 mm x 86 mm

Ignition

• SmartCraft PCM 112 Digital Inductive

Cooling system

• Water-cooled with thermostat

Gear shift

• F-N-R

Gearcase options

• 5.44"

Trim system

Power trim and tilt

Exhaust system

• Through prop

Counter Rotation

Available

Color

Phantom Black

Lubrication system

Integrated wet sump

Oil Capacity

• 7.0 Quarts / 6.6 Liters

Maximum Trim Range

• 20° (-6° to 14°)

Maximum Tilt Range

• 73° (-6° to 67°)

Engine Details

Engine Make Displacement Horse Power

Mercury 4.6

250