Phone: (07) 4927 9150 Email: rifen.boats@bigpond.com Website: www.rifenmarine.com.au



| Boat Details | | | |
|--------------|-------------------|--------------|----------------------------|
| Price | POA | Boat Brand | Mercury |
| Model | 300 HP | Length | 0.00 |
| Year | 2021 | Category | Boat Engines and Outboards |
| Hull Style | | Hull Type | |
| Power Type | | Stock Number | 0 |
| Condition | New | State | Queensland |
| Suburb | NORTH ROCKHAMPTON | Engine Make | Mercury |

Description

The new Mercury 300hp FourStroke is precision engineered from skeg to cowl. Packed with advanced technology to improve all aspects of performance and reliability. the Robust 4.6 Litre V-8 engine is designed to minimise weight and maximise fuel economy. Delivering Mercury's best ever FourStroke hole shot, top speed and fuel efficiency. The 300hp FourStroke now comes with a 3+3=6 Year factory warranty.ENGINE DETAILS

These robust motors deliver Mercury's best-ever FourStroke hole shot, top speed and fuel efficiency. Great for aluminum fishing, deck, inflatable rigid hull, inshore fishing, offshore fishing and runabouts and tritoons.SPECIFICATIONS - 300 HP / kW

• 300 / 224

Engine type • V-8

MidSection • Conventional MidSection

Displacement (CID/CC) • 279 CID

Displacement (L)

•4.6L

Cylinder Configuration • V-8 [64 degree] with Dual Overhead Cam [DOHC] and 32-valves

Full throttle RPM • 5200-6000

Air induction • Performance-Tuned Long-Runner Intake Manifold

Fuel induction systemElectronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization

Alternator amp / Watt • 85-amp (1071 Watt) with Idle Charge

Recommended fuel

• Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum

Recommended oil

• NMMA Certified FCW SAE 10W-30

Engine protection operator warning system

SmartCraft Engine Guardian

Compatible with SmartCraft digital technology • Yes

Starting • Electric Start with SmartStart Protection

Controls

• Remote Mechanical or Digital Throttle & Shift (DTS)

Steering

Hydraulic (standard)

• Power (optional)

Shaft length

• 20" / 508 mm

• 25" / 635 mm

Gearcase ratio

• 1.75:1

Dry weight *Lightest model available • 527 lbs / 239 kgs

CARB star rating • 3

Bore and stroke • 3.6 in x 3.4 in / 92 mm x 86 mm

Ignition • SmartCraft PCM 112 Digital Inductive

Cooling system • Water-cooled with thermostat

Gear shift

• F-N-R

Gearcase options • 5.44"

Trim system • Power trim and tilt

Exhaust system

Through prop

Counter Rotation

Available

Color

- Cold Fusion White
- Pearl Fusion White
- Phantom Black
- Warm Fusion White

Lubrication system

Integrated wet sump

Oil Capacity • 7.0 Quarts / 6.6 Liters

Maximum Trim Range • 20° (-6° to 14°)

Maximum Tilt Range • 73° (-6° to 67°)

Engine Details

Engine Make Displacement Horse Power Fuel Type Steering Mercury 4.6 300 Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum Hydraulic (standard) Power (optional)